

Dotec-Audio DeeGraphComp

User's Guide

About DeeGraphComp

Thank you for purchasing Dotec-Audio DeeGraphComp!

DeeGraphComp is a stunning compressor plugin with various special features:

- Can be change dynamics on each levels like a GraphicEQ.
- Can be set compress and expand on each levels.
- Can be make original compression curves by setting sliders.
- You can make spacial compressor and creative effects.

Installation on Windows OS

1. Those plug-ins are provided as a .dll and .vst3 and .aaxplugin folder (AAX).
2. To install the plug-ins, simply copy it to your system's shared VST or VST3 or AAX folder.
AAX folder : *C:¥Program Files¥Common Files¥Avid¥Audio¥Plug-Ins*
3. If you're not sure where that is, please consult your music software's documentation.
4. If your music software is already running, you'll probably need to quit and restart if before the plugin is recognised.
5. Some plug-ins come in 32-bit and 64-bit versions. If you're not sure which to use, please consult your music software's documentation.

Installation on MacOS

1. Those plug-ins are provided as a .vst (VST) and .component (AU) files and .aaxplugin (AAX) files.
2. To install the plug-ins, open “**install.pkg**” and follow the installer instructions.
3. If your music software is already running, you'll probably need to quit and restart before the plugin is recognised.

Panel Description



Enable/Disable Switch (Lightning Switch)

Enables/Disables DeeGraphComp.

RESET

Reset the position of each sliders.

-30 to -3dB sliders

You can set compress or expand to each levels.

example: When -30dB slider set to upward from -30dB, It will be expand.

INPUT

Can adjust input gain from -20dB to +20dB.

Resets to 0dB when you double click on INPUT fader.

SHAPE

Can adjust harder or softer curves. 100 is hardest.

ATTACK

Can adjust attack time from 0ms to 100ms.

Compression starts gradually after this attack time.

RELEASE:

Can adjust release time to 15ms to 300ms.

Compression stops gradually after this release time.

OUTPUT

Can adjust output gain from -20dB to +20dB.

Resets to 0dB when you double click on OUTPUT fader.

How to Register

The DOTEK-AUDIO product becomes the "**product version**" by registering the serial key and e-mail address in the "**demo version**".

This section describes how to register the serial key you purchased.

Step 1



You can register serial key by clicking registration button.

Step 2

A screenshot of the 'Registration' dialog box. The title bar says 'Registration'. The text inside says 'Please enter the serial key and your e-mail address for the registration.' There are three input fields: 'Serial key', 'E-mail address', and 'E-mail address(Verify)'. Each field has a red arrow pointing to it. At the bottom, there are three buttons: 'Open the shopping page', 'Cancel', and 'OK'. The 'OK' button is highlighted with a red rectangle.

This window will be displayed.

Please enter a serial key and your email address in the textbox and click OK button.

*** The registration requires an internet connection.**