

DOTEC-AUDIO BROADCAST PACK

User's Guide

About BROADCAST PACK

Thank you for choosing Dotec-Audio BROADCAST PACK.

This package includes “Maximizer **DeePopMax**”, “Equalizer **DeeEQ**”, “Auto leveler **DeeTrimCast**”.

Installation on Windows OS

Unzip the downloaded file and execute the included "Setup.exe".

The plug-in files are installed in the following folders.

VST2

64-bit: *C:\Program Files\Common Files\VST2*

VST3

64-bit: *C:\Program Files\Common Files\VST3*

AAX

C:\Program Files\Common Files\Avid\Audio\Plug-Ins

Installation on MacOS

1. Those plug-ins are provided as a .vst (VST) and .component (AU) files and .aaxplugin (AAX) files.
2. To install the plug-ins, open “**install.pkg**” and follow the installer instructions.
3. If your music software is already running, you'll probably need to quit and restart before the plugin is recognized.

About DeePopMax

DeePopMax is a plugin with following features:

- Adjust the balance and sound pressure simply by raising the main throttle.
- WARMTH function to add warmth at increasing loudness.
- MONITOR function to check the effect with constant level.
- Nice "Fancy" graphics.

Panel Description



Enable/Disable Switch (Lightning Switch)
Enables/Disables DeePopMax.

MAIN

Add loudness. Clicking number display to changing display in dB from %.

WARMTH

Add warmth to sound. Ranges from 0 to 100%.

OUTPUT

Control the output level. 0 to -20dB.

MONITOR(lower right of OUTPUT)

Constants volume level of input&output for monitoring

About DeeEQ

DeeEQ is a plugin with following features:

- DeeEQ is possible to equalizing with the impact only raise or lower the slider.
- Can be setting the treble side, the bass side intuitively .

Panel Description



Enable/Disable Switch (Lightning Switch)
Enables/Disables DeeEQ.

EQ
Up to boost, and down to cut. .(-100 to 100%)

TONE
Right to treble(High), and left to bass(Low).

About DeeTrimCast

DeeTrimCast is a simple plugin which controls the volume from -12dB to +3dB. It can keep the output level constant from any input level.

Panel Description



Enable/Disable Switch (Lightning Switch)
Enables/Disables DeeTrimCast.

Main Indicator

It glows red when audio is being output.

PreAmp

Amplifies the input level. (dB)

NoiseSens

Adjusts the noise level during silence.

RATIO

Adjusts the strength of the automatic volume control.

AutoDetect

Press to adjust NoiseSens automatically.

MUTE

Mutes the sound.

Main Fader

Adjusts the target output level. (dB)

How to adjust:

1. Turn up the microphone input of the audio interface until the yellow light of the **PreAmp** glows when you speak into the microphone. If it is not adjustable, turn it up on the **PreAmp**.
2. Turn up **NoiseSens** until the main indicator does not light up when you do not speak into the microphone. Or press AutoDetect.

How to Register

The DOTEK-AUDIO product becomes the "**product version**" by registering the serial key and e-mail address in the "**demo version**".

This section describes how to register the serial key you purchased.

Step 1



You can register serial key by clicking registration button.

Step 2

Registration

Please enter the serial key and your e-mail address for the registration.

Serial key

E-mail address

E-mail address(Verify)

This window will be displayed.

Please enter a serial key and your email address in the textbox and click OK button.

*** The registration requires an internet connection.**